

## Declaration of Performance

No.: 005-LICPR-150201

1.	Unique identification code of the product- type	LINITHERM PGV 026 CS120	
2.	Type, batch or serial number for the identification of the construction product as required under Article 11 paragraph 4	See label	
3.	Intended use	Thermal insulation product for buildings	
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 paragraph 5	LINITHERM Dämmsysteme Linzmeier Bauelemente GmbH Industriestr. 21 88499 Riedlingen T +49 (0) 7371 1806-0 F +49 (0) 7371 1806-96 Info@Linzmeier.de www.Linzmeier.de	
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 paragraph 2		
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3	
7.	Name and identification number of the notified body and description of the third party tasks as set out in Annex V and reference to issued certificate of constancy of performance, certificate of conformity for the factory production control (German Chamber of Public Accountants), test and calculation reports – where relevant	No. 0751 FIW München Lochhamer Schlag 4, 82166 Gräfelfing	



## 8. Declared performance

Essential characteristics	Performance		Harmonised technical specification	
Reaction to fire	Fire class	E	EN 13501-1	
Thermal resistance	See label			
Thermal conductivity	Nominal value of $\lambda_D$ in W/(m·K)	0,026	EN 12667 or 12939	
Thickness	Nominal thickness range	≥ 80 mm < 120 mm	EN 823	
·····exives	Tolerances for the thickness	T2		
Compressive stress or compressive strength	Compressive stress or strength under 10% compression	120 kPa	EN 826	EN 13165:2013
suengin	Level	CS(10\Y)120		IN 13
Tensile strength perpendicular to the panel surface	Tensile strength perpendicular to the panel surface	npd	EN 1607	ш
parier surface	Level	npd		
Dimensional stability under defined	Level	DS(70,90)3	EN 1604	
temperature and humidity conditions	Level	DS(-20,-)2	EN 1604	
All other properties		npd		

## 9. Declaration

The performance of the product ic	lentified in points 1 and 2 is in conformity with the declared performance in
point 8. This declaration of perform	mance is issued under the sole responsibility of the manufacturer identified in
point 4.	$\cap$

	//
Signed for and on behalf of the manufacturer by:	$\Lambda / /$
Dipl. Ing. Andreas Linzmeier, Managing Director (name and function)	
Riedlingen, 01/02/2015	/ Manney /
(place and date of issue)	(signature)